

BULLETIN

Slab Penetrations Buildings A, K, L, P, S, T, V and W

(11/10)

This bulletin shall serve as the criteria for slab penetrations (ceiling level above) at the Post Tension structures for buildings A, K, L, P, S, T, V and W.

There shall be no anchors, screws or other items drilled or shot into the slab with embedment into the concrete greater than 1”.

Any proposed new slab penetrations greater than 1” in the above buildings must be coordinated with landlord, and engineered by the Engineer of Record and field verified by x-ray to miss structural tendons.

The following steps must be followed to make a determination if penetration is possible:

- In Phase I (Bldgs A, K, L and P) Tenant must hire Shenberger & Associates directly to review locations.
- Shenberger will require a plan identifying the size and location of the proposed penetration dimensioned to structure. Some reviews may require x-rays.

Submit request directly to and copy the assigned Tenant Coordinator:

Shenberger & Associates
8221 Brecksville Road
Brecksville, OH 44141
440-526-3100
sai@nacs.net
Contact: Joe Kopczynski

- In Phase II (Bldgs S, T, V and W) Tenant must hire Brockette Davis Drake directly to review locations.
- Brockette Davis Drake will require a plan identifying the size and location of the proposed penetration dimensioned to structure. Some reviews may require x-rays.

Submit request directly to and copy the assigned Tenant coordinator:

Brockette Davis Drake, Inc.
Attn: Gary Taylor, PE
4144 North Central Expressway
Suite 1100
Dallas, TX 75204
214.824.3647